

1 Initialise THLA : pointer de VA

```

HLINIT: LEA SOURCE, A1
        MOVE.L (A1)+, A0
HLINIT: MOVE.L SOURCE, A0
        LEA THLA, A1
        MOVEQ #23, D0
        MOVEQ #"\", D2
        MOVEQ #"A", D3
        CLR.L THLCOM-THLA(M)
        BRA GEY80A
  
```

```

GEY80: TST.B (A0)+
        BNE GEY80
  
```

```

GEY80A: CMP.L A2, A0
        BGE GEY81
        CMP.B (A0), D2
        BNE GEY80
        ADDQ #1, A0
        CMP.B (A0), D3
        BNE GEY80
        SUBQ #1, A0
        MOVE.L A0, (A1)+
        DBRA D0, GEY80
  
```

```

GEY81: MOVE.L $436, (A1)
        CMP #23, D0
        BNE GEY82
        MOVEQ #84, D0
        BRA RER
  
```

```

GEY82: RTS
  
```

```

GEY82: MOVE.L THLA, A0
        CLR D6
  
```

(A1)
 MOVE.L SOURCE, A2
 SUBQ #2, A2

24 mots

CLR.L THLCOM-THLA(M)

BRA GEY80A

cherche @\A

fin

MOVE.B (A0), D2

(A2)
 ADDQ.L #2, (A1)

certs sont le même

} fichier help sans VA

ôte mot clef

✓